

ImagePerfect™ 7103 / 7104 / 7105

Chrome 85 EXT / Chrome 70 EXT / Chrome 40 EXT

Solar control films for exterior use on buildings to reduce the greenhouse effect, delivering heat and light control.

ImagePerfect™ 7103 Chrome 85 EXT, ImagePerfect™ 7104 Chrome 70 EXT and ImagePerfect™ 7105 Chrome 40 EXT are solar control films for up to 12 year exterior use. They will reduce the room temperature and thereby improve the personal well-being in work spaces and/or living areas. The films incorporate a reflective surface with the one-way mirror effect providing privacy and a contemporary look on any building exterior. They are extremely effective at reducing solar heat gain whilst continuing to allow some natural light transmission. The films also help to improve the heating, ventilation and air conditioning (HVAC) system, improving overall efficiency and thereby reducing costs. They can also help to reduce the risk of skin cancer. As such, amongst other environments, they will be used in private households, offices, retail locations, schools and government agencies, where they will be applied on the outside surface of the glass. They utilise a high-quality PET film with high optical qualities and a hard, scratch-resistant surface for durability and ease of maintenance during window cleaning. They must be wet applied.

Attention: To avoid possible glass breakage, please contact your local ImagePerfect distributor before installation. Do not clean for at least 1 month after application and do not apply any type of sticker or adhesive on the film.

Specifications			
Description	IP 7103	IP 7104	IP 7105
Installation	Exterior	Exterior	Exterior
Colour From the Outside	Light Silver	Light Silver	Light Silver
Durability (Vertical Application)	12 years	12 years	12 years
Thickness	60mym	60mym	60mym
Film Composition	PET	PET	PET
Solar Energy Reflection	66%	53%	25%
Solar Energy Absorption	23%	26%	32%
Solar Energy Transmission	11%	21%	43%
Total Solar Energy Rejected	84%	71%	53%
Visible Light Transmission	16%	30%	59%
g-Value	0.14	0.29	0.50
UV Transmission (300-380NM)	< 1%	< 1%	< 1%
Edge Sealing, Vertical (25-89°)	Mandatory	Mandatory	Mandatory
Flame Retardancy	M1	M1	M1
Pendulum Test EN 12600	N/A	N/A	N/A
Security Glazing EN 356	N/A	N/A	N/A
Shelf Life (Storage at -5°C to +40°C)	3 years	3 years	3 years

© February 2021 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading. Spandex gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Spandex's general terms and conditions of sale. Spandex's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Spandex be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.