

INCREASE VISIBILITY IN LOW-LIGHT CONDITIONS, DIN 20471 CERTIFIED.

Reflective heat transfer material is thin with a reflective finish.



AVAILABLE IN

50 cm x 25 m rolls

RECOMMENDED FABRICS

- 100% Cotton
- 100% Polyester*
- Polyester-Cotton blends

* Test before application!

IMPORTANT

Please remove the protection carrier before cutting.

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 3 mm for lettering and logos.

APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 5 sec.
- Pressure: Medium (#4-6 on Hotronix®)
- Peel: Hot
- Repressing: 5 sec.

MULTI-COLOR DESIGNS

CAD-CUT® Reflective is not suitable for multi-layer application.

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry clean. Iron only inside out.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS



KEY

Easy weed	Thin
Ironable	Sticky carrier
Ironable only inside out	Multi-color application
Washable	Peel hot
Sublimation	Application
Stretchable	Pressure
Flock	



silver reflective