

TITAN BLITZ | TBW-100

High tack gloss white print vinyl developed for shorter term applications on powervehicles. Combine with our lamination film TITAN LAM 250 GLOSS.

FACE FILM

Monomeric PVC, gloss white

Thickness (µm)	100	
Tensile strength (N/mm ²)	>58	DIN EN ISO 527
Elongation at break (%)	>170	DIN EN ISO 527

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	21	
24 hours (180°) N/25mm	28	

RELEASE LINER

Lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140	
--------------	-----	--

PRODUCT APPLICATION

Dimensional stability (.mm)	<1,2	FINAT FTM 14
Application temperature (°C)	10 to 25	
Service temperature (°C)	-10 to 70	

DURABILITY

Outdoor durability (years)	3	Northern-EU climate, vertical exposure
----------------------------	---	--

ROLL SIZES

1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.